

Product: Comfi Lay 5

Technical Data Sheet for Foam Underlay – AXICOMFILAY5D

Description of Goods

Foam commercial underlay suitable for installation using the double stick or dual bond method of Signature Axminster Carpet on concrete floors (refer to adhesive manufacture specifications for application and guidelines)

ROLL DIMENSIONS	LENGTH	WIDE	M² PER ROLL
	20	1.37	27.4
Weight	26kg per roll		
Thickness	5.0mm +/-10%		
TOP SURFACE	Stitchbrown, Kraft paper		
BOTTOM	Non woven fabric		

Tensile Strength & Elongation		L	W
i) Mean load at breaking point	ISO 9073.3-1989	197.1 N/50mm	30.3 N/50mm
ii) Mean elongation at 40 N		3%	N/A
Tested at Standard Conditions			
i) Mean elongation at break		18%	3.50%
Thickness Loss on Static - Long Term Loading			
Compliance to	AS4288-2003	PASS	Table 2
Soft Underlays for Textile Floor Coverings - Method for the Determination of Compress Characteristics			
Compliance to	AS42800-2003	PASS	Table 2
Under Lay Thickness			
Compliance to	AS42800-2003	PASS	Table 2
Textile Floor Covering - Mass Per Unit Area			
Weight per 400 cm ²	1085 g/m ²	+/- 2.0%	
Resistance to Breaking/and Cracking			
No cracks or breaks	AS42800-2003	PASS	Table 2
Length of cracks or breaks	AS42800-2003	PASS	Table 2
Location of cracks or breaks	AS42800-2003	PASS	Table 2

NOTE

Specification are subject to change without notice, refer to our webiste for the latest information or technical bulletin