



## sustainable, fashionable flooring designed for all interiors

innovation & inspiration

ignature \*commercialLVT

## THE BEST ACOUSTIC WOVEN VINYL FLOORING





**FABRIC** arrange 2727



**FABRIC** dimension 2622



**FABRIC** scheme 5215



**FABRIC** motion 4213



**FABRIC** map 2741



**FABRIC** create 2646



**FABRIC** purpose 2695



**FABRIC** breathe 2685



**FABRIC** flex 2444



**FABRIC** pulse 1259



FABRIC resolve



**FABRIC** formulate 2535



FABRIC rise 1258



FABRIC touch 1260



FABRIC dash 2653



**FABRIC** current 1255



**FABRIC** enrich 1257



FABRIC flow 1263



**FABRIC** circulate 1254



**FABRIC** evolve 1256



**FABRIC** compose 1262

## Fabric





product tile size total thickness carton size total weight slip rating fire rating ISO 9239.1 scratch resistance dimensional stability backing acoustic insulation

wovn™ vinyls, fabric 500mm x 500mm 5.0mm 4sqm 3.0kg/m<sup>2</sup> P1/R9 7.6 kw/m<sup>2</sup> critical radiant flux class T contains fibre glass layer felt

underfloor heating recommended adhesive installation method

co-ordinates with traffic warranty fire environmental sustainability availability

suitable PS with V1 trowel ashlar, brick, quarter turn

all wovn vinyl tiles & Themo Bak™ carpet tiles class 33 heavy duty commercial 15 year commercial suitable all areas sustainable manufacturing 10% recycled content in stock

**Traffic** 



Warranty



19dB

















au 03 9401 0888 nz 0800 150 555 signaturefloors.com.au signaturefloors.co.nz