

FIELD**TILES**



a true palette of contemporary shades



innovation & inspiration

| *Signature*[®]
floorconcepts

a true palette of contemporary shades

FIELD**TILES**



field pebble 400



field slate 300



field granite 200



field rock 100



field bluestone 500

product
construction
yarn/fibre
pile weight
pile height
gauge
tile size
total thickness
carton size
total weight
dimensional stability
backing
electrostatic propensity
fire rating ISO 9239.1
recommended adhesive
installation method
availability
Comfi Bak® option
customise Shapes™
traffic
warranty
fire
stain/soil
sustainability

field
 level loop
 solution dyed nylon
 540 g/m² (16oz)
 3.0mm
 5/64
 500mm x 500mm
 5mm
 5m²
 4540 g/m²
 <0.15%
 Thermo Bak™
 <3.0kv
 >4.5 kw/m² critical radiant flux
 RLA Polymers GS300
 quarter turn
 in stock
 50m² minimum
 50m² minimum
 extra heavy duty commercial
 15 year
 suitable all areas
 Ultra Gard®
 GreenTag® GreenRate Level A certified
 EPD and Declare labels



au 03 9401 0888
 nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Product may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Technical Information Manual, Maintenance Guide & Warranty Guide for further clarification. 07/2022©