

NETWORK **PLANKS**



innovation & inspiration

Signature[®]
floorconcepts

for 100% GreenStar Points

NETWORK **PLANKS**



protocol
NETWORK100PLFB

gridline
NETWORK200PLFB

junction
NETWORK300PLFB

pulsewave
NETWORK400PLFB

synapse
NETWORK500PLFB

construction
yarn/fibre
pile weight
pile height
gauge
tile size
total thickness
carton size
total weight
dimensional stability
backing
electrostatic propensity

multi-level loop
solution dyed nylon
542 g/m² (16oz)
3.5mm
1/10
250mm x 1000mm
6mm
5m²
3 kg/m²
<0.15%
Flexi Bak
<3.0kv

fire rating ISO 9239.1
recommended adhesive
installation method
availability
Thermo Bak® option
Comfi Bak® option
customise Shapes®
ACCS rating
warranty
fire
stain/soil
sustainability

6.7 kw/m² critical radiant flux
RLA Polymers GS300
brick, ashlar, herringbone, basketweave
in stock
50m² minimum
50m² minimum
50m² minimum
commercial heavy duty
15 year
suitable all areas
Ultra Gard
GreenTag® Green Rate Level A
EPDs and Declare labels
WELL & LBC eligible



Declare.
circul8
LOCAL RECYCLING INITIATIVE

Signature
floorconcepts®

au 1800 150 554
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Product may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Technical Information Manual, Maintenance Guide & Warranty Guide for further clarification. 03/2024©