

PAVEMENT **PLANKS**



a true palette of contemporary shades



innovation & inspiration

| Signature[®]
floorconcepts

a true palette of contemporary shades

PAVEMENT **PLANKS**



pavement stone 400



pavement cement 300



pavement ash 200



pavement coal 100



pavement ink 500

product	pavement
construction	multi-level loop
yarn/fibre	solution dyed nylon
pile weight	612 g/m ² (18oz)
pile height	3.5mm
gauge	1/10
tile size	250mm x 1000mm
total thickness	5.5mm
carton size	5m ²
total weight	4612 g/m ²
dimensional stability	<0.15%
backing	Thermo Bak™
electrostatic propensity	<3.0kv
fire rating ISO 9239.1	>4.5 kw/m ² critical radiant flux
recommended adhesive	RLA Polymers GS300
installation method	ashlar, herringbone, basket weave
availability	in stock
Comfi Bak® option	50m ² minimum
customise Shapes™	50m ² minimum
traffic	extra heavy duty commercial
warranty	15 year
fire	suitable all areas
stain/soil	Ultra Gard®
sustainability	GreenTag® GreenRate Level A certified EPD and Declare labels



au 03 9401 0888
nz 0800 150 555
signaturefloors.com.au
signaturefloors.co.nz

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Product may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Technical Information Manual, Maintenance Guide & Warranty Guide for further clarification. 07/2022©