





aboard wide board









Lulea Oak

ABODERG543



Floro Oak

ABODERG545



Tromso Oak **ABODERG539**



Vardo Oak

ABODERG540



Boden Oak **ABODERG542**



Malmo Oak **ABODERG544**



TECHNICAL SPECIFICATIONS

Plank Size 223 x 1813mm

Total Thickness 5.50mm
Wear Layer 0.55mm

Wear Layer Treatment Quartz enhanced PUR coating

Surface Natural embossed, true to life oak boards

Edge Design Micro V groove 4 sided
Fire Rating ISO 9239.1 12.1 kW/m² critical radiant flux

Slip Rating

Underfloor Heating Suitable for water based systems

Planks per Box 6 pcs/box (2.43m²)

Installation Method Tight Lock - no underlay - min. floor prep required ^Δ

Lifetime Residential, 15 Yr Commercial



Abode has been tested and certified to comply with strict indoor quality emission requirements.



Warranty



















- installs directly over irregularities and existing floors
- can be laid over ceramic and porcelain tiles
- can be laid over concrete
- can be laid over chipboard and tongue & groove flooringexisting floors need to adhere to the sub-floor
- existing floors need to adhere to the sub-floor
- existing floor cannot be cushioned
- \bullet uneven floors require sub-floor preparation when there is a height variation more than 3mm over 1m $^{\vartriangle}$
- sub-floors should be clean and dry

 ${\it Please \ refer \ to \ installation \ guidelines; if \ uncertain \ seek \ clarification \ prior.}$



au 03 9401 0888 nz 0800 150 555 signaturefloors.com.au signaturefloors.co.nz

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification.