

SIGNATURE FLOORS SHEET VINYL BPIR DECLARATION

Version 1.0 February 2024



DESIGNATED BUILDING PRODUCT: Class 1

DECLARATION

Signature Floorcoverings Pty Ltd (branded as Signature Floors) has provided this declaration to satisfy the provisions of the **Building (Building Product Information Requirements) Regulations 2022**.

COMPANY DETAILS

Name	Signature Floorcoverings Pty Ltd
Role	Supplier
NZBN	9429041854273
Address	15 Bath St, Parnell, Auckland 1052
Website	www.signaturefloors.co.nz
Email	info@signaturefloors.co.nz
Phone	09 414 2001

DESCRIPTION OF BUILDING PRODUCT

Signature Floors supplies a range of sheet vinyl flooring for use as an impervious lining in residential, low traffic environments and use.

Sheet vinyl is a synthetic material made primarily of polyvinyl chloride (PVC) resins. The material is then coated in a UV-cured surface such as polyurethane (PU).

Signature Floors sheet vinyl is supplied with a decorative finish to reproduce the look of tile, stone or timber flooring.

The flooring may be used in conjunction with underfloor heating providing that insulation is provided so that the surface temperature to which the flooring is exposed does not exceed 27°C.

Slip resistance needs to be considered in respect of access routes. **Access routes** are defined as a continuous route that permits people and goods to move between the apron or construction edge of the building to spaces within a building, and between spaces within a building.

All Signature Floors sheet vinyl must be fully adhered with all joins welded. They may not be loose laid.

They are to be installed to Signature Floors sheet vinyl installation guidelines and to NZ Flooring Standards NZS AS1884:2013. Signature Floors recommends several adhesive options.

Depending on installation, Signature Floors sheet vinyl may contribute to absorbing sound.

Signature floors sheet vinyl collections

FLOORTEX

Floortex is a 2.00 mm thick sheet vinyl with a wear layer of 0.20 mm. It is supplied in 2 and 3 m widths in a range of tile, stone and hardwood timber effects.

Slip resistance has been evaluated using the oil wet inclining platform slip-resistance (Appendix D, NZ 4586). It achieves R11 and is therefore not recommended for use in access routes liable to become wet during use.

Testing for critical heat flux has not been carried out and so Floortex should not be installed where building code performance clause C3.4 (b) applies.

See [here](#) for more information.

AVIGNON

The Avignon range of sheet vinyl flooring is a 2.40 mm thick sheet vinyl with a wear layer of 0.35 mm. It is supplied in 2 and 3 m widths in a range of stone and hardwood timber effects.

When laid, it will absorb sound up to a level of 16dB.

Slip resistance has not been evaluated and is therefore not recommended for use in access routes liable to become wet during use.

Testing for critical heat flux has not been carried out and so Avignon should not be installed where building code performance clause C3.4 (b) applies.

See [here](#) for more information.

VOGUE

The Vogue range of sheet vinyl flooring is a 2.40 mm thick sheet vinyl with a wear layer of 0.35 mm. It is supplied in 2 and 3 m widths in a range of hardwood timber effects.

When laid, it will absorb sound up to a level of 16dB.

Slip resistance has not been evaluated and is therefore not recommended for use in access routes liable to become wet during use.

Testing for critical heat flux has not been carried out and so Vogue should not be installed where building code performance clause C3.4 (b) applies.

See [here](#) for more information.

Signature Floors, originally an Australasian company, was founded in 1989. It has begun working towards sustainability. The Australian arm is certified **Carbon Neutral**, and most products are Green Tag Certified and/or have a Declare label. In 2023 it was purchased by the **Beaulieu International Group** (BIG). BIG has an active focus on **sustainability** and have developed a strategy to achieve a zero footprint by 2030. As part of the BIG group, Signature Floors is now part of this approach.

CONTRIBUTION TO BUILDING WORK CODE OBLIGATIONS

Signature Floors relies on third party testing and the in-service history of sheet vinyl to make the following performance claims.

When installed to Signature Floors sheet vinyl installation guidelines and to NZ Flooring Standards NZS AS1884:2013, Signature Floors sheet vinyl *may* contribute to compliance with the applicable performance criteria in respect of:

- B1 (Structure): B1.3.1, B1.3.2, B1.3.3 (a, b, e, j, q)
- B2 (Durability): B3.2.1 (c)
- C3 (Fire Affecting Areas Beyond The Fire Source): C3.4 (b)
- D1 (Access Routes): D1.3.3 (d)
- E3 (Internal Moisture): E3.3.3, E3.3.5, E3.3.6
- F2 (Hazardous Building Materials): F2.3.1

FOR FURTHER INFORMATION

Signature Floors sheet vinyl range of products must be used in accordance with all Signature Floors requirements.

For supporting information refer to **Signature Floors**.

RESPONSIBLE PERSON

In accordance with Regulation 8, as the responsible person I confirm that the information supplied in this declaration is based on information supplied to the company as well as the company's own processes and is therefore to the best of my knowledge, correct.

I can also confirm Signature Floors sheet vinyl products, as referred to in this statement, are not subject to a warning or ban under **s26 of the Building Act**.

Signed for and on behalf of Signature Floorcoverings Pty Ltd (branded as Signature Floors):

Richard Slade

Richard Slade
GENERAL MANAGER (NZ)

February 2024

SIGNATURE FLOORCOVERINGS PTY LTD

15 BATH ST, PARNELL, AUCKLAND 1052

09 414 2001 | www.signaturefloors.co.nz

Uncontrolled in printed format

Signature
signaturefloors