

Signature[®]
signaturefloors

dimension
Hybrid Flooring



OAKS, AUSSIE SPECIES & TILES

FOR TIMELESS STYLE AND
EASY EVERYDAY LIVING



Featuring fast and easy
to install click system

Oaks

Aussie Species

Tiles



Locke Oak DIMENSION02 | **Marx Oak** DIMENSION03 | **Kant Oak** DIMENSION01 | **Blackburn Spotted Gum** DIMENSION07 | **Aristotle Blackbutt** DIMENSION04 | **Cartwright Spotted Gum** DIMENSION08 | **Hume Spotted Gum** DIMENSION05 | **Stuart Mill Spotted Gum** DIMENSION06 | **Confucius** DIMENSION09 | **Aquinas** DIMENSION10

TECHNICAL SPECIFICATIONS

Plank Size	228 x 1830mm
Total Thickness	7mm (5.5mm board & 1.50mm backing)
Wear Layer	0.50mm
Wear Layer Treatment	Quartz enhanced PUR coating
Surface	Natural embossed, true to life oak boards
Edge Design	Micro V groove 4 sided

Fire Rating ISO 9239.1	Suitable all areas
Slip Rating	P3
Underfloor Heating	Suitable for water based systems
Planks per Box	4 pcs/box (1.669m ²)
Installation Method	5G - no underlay required
Warranty	25 Yr Residential, 10 Yr Commercial

- installs directly over irregularities and existing floors
- can be laid over ceramic and porcelain tiles
- can be laid over concrete
- can be laid over chipboard and tongue & groove flooring
- existing floors need to adhere to the sub-floor
- existing floor cannot be cushioned
- uneven floors require sub-floor preparation when there is a height variation more than 3mm over 1m*
- sub-floors should be clean and dry

* Please refer to installation guidelines; if uncertain see clarification prior.

