

Distinct Hybrid Flooring







Distinct Hybrid Flooring

Oaks Aussie Species



TECHNICAL SPECIFICATIONS

DISTINCT08

Plank Size 1220 x 228mm

Thickness 6mm Wear Layer 0.50mm

Wear Layer Treatment Quartz enhanced PUR coating

Backing Liteback

Pack Size 10 pcs/box (2.78m²)

Subfloor Heating Suitable for water based systems

DISTINCT07

DISTINCT09

Slip Resistance P

Fire Rating ISO 9239.1 Suitable all areas

Locking System 50

• installs directly over irregularities and existing floors

- can be laid over ceramic and porcelain tiles
- can be laid over concrete
- can be laid over chipboard and tongue & groove flooring
- \bullet existing floors need to adhere to the sub-floor
- existing floor cannot be cushioned
- uneven floors require sub-floor preparation when there is a height variation more than 3mm over 1m*

DISTINCT**05**

• sub-floors should be clean and dry

* Please refer to installation guidelines; if uncertain see clarification prior.







DISTINCT10







au 03 9401 0888 nz 0800 150 555 signaturefloors.com.au signaturefloors.co.nz

Terms & Conditions: Specifications are subject to manufacturing tolerances and may be changed without prior notice. Dye lots may vary in colour from sample and between production lots. All product purchases are subject to Signature Floorcoverings Standard Terms & Conditions of Sale. Please refer to our Installation Guideline, Maintenance Manual and Warranty Document for further clarification.